

# HEAVY LINES

## Corpo

- in alluminio verniciato a polveri.  
 • Frame: In aluminium powder coated.  
 • Gehäuse: Aus Aluminiumpulver gepulvert.  
 • Corps: En aluminium poudre peinte.  
 • Cuerpo: en aluminio polvo pintado.

## Lenti

- con vetro temprato di protezione per garantirne la carrabilità a 2000 Kg.  
 • Optics: With tempered protection glass to guarantee the driver-over resistance up to 2000kg.  
 • Linsen: Mit gemäßigt Schutzabdeckung, befahrbar bis 2 t.  
 • Optiques: Avec verre tempérées de protection pour garantir la résistance a 2000Kg.  
 • Lentes: con vidrio templado de protección para garantizar el paso a 2000 Kg.

## Cavo

- Neoprene 3 m.  
 • Cable: Neoprene 3m.  
 • Kabel: Neopreno 3m.  
 • Câble: Néoprène 3m.  
 • Cable: Neopreno 3m.

## PG9

- Pressacavo in ottone nichelato.  
 • Cable gland in nichel brass.  
 • Gland in nichel messing.  
 • Glante en laiton nichelè.  
 • Pressastopa en latón Niquel.

# HEAVY LINES

## DRIVE-OVER PROFILES




### FIXING




### PHOTOMETRICAL CURVES


10°




30°




50°




70°



120°



WALLWASHER




Le curve fotometriche si riferiscono a Rabal 18 LED bianco freddo e sono indicative  
 Photometric curves refer to the Rabal 18 LEDs cold White and are indicative

## RABAS

C.C.



**LED:** POWER  
**EMISSION:** ASYMMETRIC - 10° - 30° - 50°  
 - 70° - 120° - WALLWASHER  
**COLOUR:** MONO  
**CABLE:** 3m NEOPRENE + PG9 CABLE  
 GLAND  
**DRIVER:** NOT INCLUDED  
**POWER:** 2W LED  
**PROTECTION:** HIGH (IP67)




**LENGHT**  
 249 mm  
 498 mm  
 995 mm  
 1180 mm

## BALMUR

C.C.



**LED:** POWER  
**EMISSION:** WALLWASHER  
**COLOUR:** RGB  
**CABLE:** 3m NEOPRENE + PG9 CABLE  
 GLAND  
**DRIVER:** NOT INCLUDED  
**POWER:** 2W LED  
**PROTECTION:** HIGH (IP67)




**LENGHT**  
 498 mm  
 790 mm

## RABAL

C.C.



**LED:** POWER  
**EMISSION:** ASYMMETRIC - 10° - 30° - 50°  
 - 70° - 120° - WALLWASHER  
**COLOUR:** MONO, RGB  
**CABLE:** 3m NEOPRENE + PG9 CABLE  
 GLAND  
**DRIVER:** NOT INCLUDED  
**POWER:** 2W LED  
**PROTECTION:** HIGH (IP67)



**LENGHT**  
 498 mm  
 790 mm

## ACCESSORIES

### OUTER-CASINGS



## SUITABLE ELECTRONICS

C.C.

### LED CONTROLGEARS



### DRIVERS



### TOUCH PANEL



### DISPLAY DMX EASY



# RABAS MONO

Profilo rettangolare fisso carrabile per esterni.  
 Applicazione con controcassa.  
 Corpo in alluminio.

*Rectangular fixed outdoor drive-over profile with outer-casing.*





*Rechteckiges, starres Profil, befahrbar, für Außenbereiche.  
 Installation mit Einbaugehäuse.  
 Gehäuse aus Aluminium.*

*Profilé rectangulaire outdoor fixe à encastrement avec boîtier  
 d'encastrement.*

*Perfil rectangular fijo transitable para exteriores.  
 Aplicación con contracaja.  
 Cuerpo en aluminio.*



PG9 doppio pressacavo per versione 3 e 6 led.  
 Double cable gland PG9 for 3 to 6 led version.




	n° led 2W	Code	Outer-casing
<b>G</b>	3	<b>86283</b>	<b>84919</b>
<b>G</b>	6	<b>86284</b>	<b>84920</b>
<b>G</b>	10	<b>86285</b>	<b>84921</b>
<b>G</b>	12	<b>86286</b>	<b>84922</b>

C.C.
600 mA
2 WATT POWER
NO LED
NO FLAME
0,920
1,650
3,000
3,600
Kg
2000 Kg
3 m
850°
IP67

Colours      Optical      Code      Controcassa - Outer Casing

● C	10°	10
● W	30°	30
● N	50°	50
● B	70°	70
● Y	120°	12
● R	Wall-Washer	25
● G		



COD **84919** → 239 mm  
 COD **84920** → 488 mm  
 COD **84921** → 985 mm  
 COD **84922** → 1170 mm

# BALMUR RGB

Profilo rettangolare fisso carrabile per esterni.  
Aplicazione con controcassa.  
Corpo in alluminio.

*Rectangular fixed outdoor drive-over profile with outer-casing.*

*Rechteckiges, starres Profil, befahrbar, für Außenbereiche.  
Installation mit Einbaugehäuse.  
Gehäuse aus Aluminium.*

*Profilé rectangulaire outdoor fixe à encastrement avec boîtier  
d'encastrement.*





*Perfil rectangular fijo transitable para exteriores.  
Aplicación con contracaja.  
Cuerpo en aluminio.*

RGB

BALMUR



PG9 doppio pressacavo per versione 3 e 6 led.  
Double PG9 cable gland for 3 to 6 led version.



	n° led	2W	Code	Outer-casing
G	3		86816	84919
G	6		86817	84920
G	12		86818	84921
G	15		86819	84922

1,500  
1,860  
2,590  
3,200

2000 Kg

3 m


C.C. 2WATT RGB

850°

IP 67

Colours	Optical	Code	Controcassa - Outer Casing
---------	---------	------	----------------------------

RGB Z Wall-Washer 25



COD 84919 → 239 mm  
COD 84920 → 488 mm  
COD 84921 → 985 mm  
COD 84922 → 1170 mm

# RABAL MONO




Profilo rettangolare fisso carrabile per esterni.  
 Applcazione con controcassa.  
 Corpo in alluminio.

*Rectangular fixed outdoor drive-over profile with outer-casing.  
 Aluminum body.*

*Rechteckiges, starres Profil, befahrbar, für Außenbereiche.  
 Installation mit Einbaugehäuse.  
 Gehäuse aus Aluminium.*

*Profilé rectangulaire outdoor fixe à encastrement avec boîtier  
 d'encastrement.*

*Perfil rectangular fijo transitable para exteriores.  
 Aplicación con contracaja.  
 Cuerpo en aluminio.*



Barra fornita con cavo 7x1 e doppia serie interna 9+9 led (utilizzare 2 alimentatori)  
 Bar sold with 7x1 cable and double internal series 9+9 leds (use 2 drivers)

	n° led 2W	Code	Outer-casing
<b>G</b>	12	<b>86826</b>	<b>84940</b>
<b>G</b>	18	<b>86827</b>	<b>84941</b>

0,920  
1,650  
3,000  
3,600

600 mA  
2 WATT  
POWER

2000 Kg

3 m

850°

IP 67

CE

III

F

9

Caution


RoHS

WEEE

C.C.

Colours      Optical      Code      Controcassa - Outer Casing

● C	10°	10
● W	30°	30
● N	50°	50
● B	70°	70
● Y	120°	12
● R	Wall-Washer	25
● G		



COD 84940 → 488 mm  
 COD 84941 → 780 mm

